




Project:	Type:
Item. No.	
Location:	
Notes:	

RD60

recessed downlight - trimless



standard features

electrical

- Input operating voltage: 120V, 60Hz
- Power cord: 18/2 SPT-2 (black)
- Compatible with Specialty Lighting On/Off Switch and Full Range Rotary Dimmer
NOTE: Not compatible with Three Level Touchdimmer
- Link up to 50 fixtures maximum

lighting source

- LED integrated technology (non-replaceable lamp)
- Initial lumens: 760
- Beam angle: 120°
- 8 Watt

dimensions

- Height: 2 $\frac{7}{8}$ "
- Diameter: 3 $\frac{1}{4}$ "

construction

- Steel

finish

- Painted: black (BK), white (WH)
- Plated: antique brass (AB), brushed nickel (BN), polished brass (PB), polished chrome (PC)

installation

- Adjustable mounting ring pre-installed 7/8" from canister opening
- Installation hole diameter 3 3/8"

warranty/certification

- 5 year warranty
- UL and cUL



RD60

ordering information

product	color temp	wiring	connector style	finish	installation method
RD60	830	2	S	PB	R
RD60	830 3000K warm	1 10' power cord with roll switch located 5' from plug 2 10' power cord with roll switch located 5' from plug & 30" extension with female connector 3 30" male & female extensions 4 30" male extension	S standard T t-shaped	AB Antique Brass BK Black BN Brushed Nickel PB Polished Brass PC Polished Chrome WH White	R ring mount

**Note: Minimums may apply for White finish*