



| | |
|-----------|-------|
| Project: | Type: |
| Item. No. | |
| Location: | |
| Notes: | |

RDF60

recessed downlight - flanged

standard features

electrical

- Input operating voltage: 120V, 60Hz
- Power cord: 18/2 SPT-2 (black)
- Compatible with Specialty Lighting On/Off Switch and Full Range Rotary Dimmer
NOTE: Not compatible with three level touch dimmer
- Link up to 50 fixtures maximum

lighting source

- LED integrated technology (non-replaceable lamp)
- Initial lumens: 760
- Beam angle: 120°
- 8 Watt

dimensions

- Height: 2 7/8"
- Diameter: 3 1/4"

construction

- Steel

finish

- Painted: black (BK), white (WH)
- Plated: antique brass (AB), brushed nickel (BN), polished brass (PB), polished chrome (PC)
- Screw Hole only available in Black (BK), Antique Brass (AB), & Polished Brass (PB) finishes

installation

- Adjustable mounting ring, spring clips, or screw holes
- Installation hole diameter 3 3/8" for the adjustable ring or screw holes
- Installation hole diameter 3 3/4" for spring clips

warranty/certification

- 5 year warranty
- UL and cUL




ring mount



spring clip



screw hole



RDF60

ordering information

| product | color temp | wiring | connector style | finish | installation method |
|---------|----------------|--|--------------------------|--|--|
| RDF60 | 830 | 2 | S | PB | R |
| RDF60 | 830 3000K warm | 1 10' power cord with roll switch located 5' from plug 2 10' power cord with roll switch located 5' from plug & 30" extension with female connector 3 30" male & female extensions 4 30" male extension | S standard T t-shaped | AB Antique Brass BK Black BN Brushed Nickel PB Polished Brass PC Polished Chrome WH White <i>*Note: Minimums may apply for White finish</i> <i>**Screw Hole ONLY available in Black, Antique Brass, & Polished Brass finishes</i> | R ring mount SC spring clip SH screw hole ** |