



Project: _____ Type: _____

Item. No. _____

Location: _____

Notes: _____

lamps

ordering information



T10 (inter)

incandescent 120 volt

bulb	base	watts	item number	description	avg rated life (hrs)	lumens
T6	med	15	398-320	15T6/C - clear	2000	100
T10	med	15	398-340	15T10/C - clear	2500	120
T10	med	25	398-520	25ETC/32 torpedo tip	1500	200
T10	med	25	398-840	25T10/C - clear	1000	260
T10	med	25	398-850	25T10/F - frosted	1000	255
R14	med	40	398-1370	40R14	1500	250
R14	inter	40	398-1320	40R14N	1500	250
S11	inter	40	398-1440	40S11N/C - clear	500	420
S11	inter	40	398-1480	40S11N/F - frosted	500	420



T10 (med)



T10 (ETC)



R14

halogen 120 volt

bulb	base	watts	item number	description	avg rated life (hrs)	lumens
T4	G8	20	398-111	120V G8 20W (xenon)	2000	N/A
T4	G8	25	251-52	120V G8 25W	2000	200
HR	med	35	398-995	35HR16	1500	385
HR	inter	35	398-970	35HR16N	1500	385



S11 (inter)



HR

halogen 12 volt

bulb	base	watts	item number	description	avg rated life (hrs)	lumens
T3	G4	10	398-95	12V G4 10W	2000	140
T3	G4	10	398-90	12V G4 10W (xenon)	2000	140
T3	G4	20	398-380	12V G4 20W (xenon)	2000	350



halogen 12v

MR-16 12 volt (halogen)

bulb	base	watts	item number	description	avg rated life (hrs)
MR-16	GU5.3	20	398-373	20MR1612V	5000
MR-16	GU10	35	398-365	35MR1612V-Flood	2000
MR-16	GU5.3	35	485-132	Q35MR16C/CG40	5000
MR-16	GU5.3	50	398-400	50MR1612V	5000
MR-16	GU5.3	50	485-133	50MR1612V-Flood	5000



MR-16



T4

fluorescent T4 (1/2" diameter)

bulb	base	watts	item number	description	nominal length	avg rated life (hrs)	initial lumens
T4	bi-pin	20	397-170	F20T4/CW	22 5/16"	8,000	1000

Note: *Slimlink* replacement lamp



T5

fluorescent T5 (5/8" diameter)

bulb	base	watts	item number	description	nominal length	avg rated life (hrs)	initial lumens
T5	bi-pin	6	485-235	F6T5/D	9"	7,500	325
T5	bi-pin	8	485-240	F8T5/CW	12"	7,500	400
T5	bi-pin	13	485-265	F13T5/CW	21"	7,500	860
T5	bi-pin	14	485-262	F14T5/CW	22"	20,000	1350
T5	bi-pin	21	485-266	F21T5/CW	34"	20,000	2100
T5	bi-pin	21	485-267	F21T5/WW	34"	20,000	2100
T5	bi-pin	28	485-268	F28T5/CW	46"	20,000	2900
T5	bi-pin	35	485-269	F35T5/CW	58"	20,000	3650



T8

fluorescent T8 (1" diameter)

bulb	base	watts	item number	description	nominal length	avg rated life (hrs)	initial lumens
T8	bi-pin	15	485-290	F15T8/WW	18"	7,500	1000
T8	bi-pin	17	485-353	F17T8/WW	24"	24,000	1350
T8	bi-pin	25	485-355.5	F25T8/N	36"	24,000	2150
T8	bi-pin	25	485-352	F25T8/WW	36"	24,000	2150
T8	bi-pin	32	485-358	F32T8/CW	48"	24,000	2850
T8	bi-pin	32	485-357	F32T8/N	48"	24,000	2850
T8	bi-pin	32	485-365	F32T8/WW	48"	24,000	2850
T8	bi-pin	40	485-359	F40T8/CW	60"	24,000	3600
T8	bi-pin	40	485-361	F40T8/N	60"	24,000	3600



LED MR16



LED PAR20



LED PAR20



LED R14

LED

bulb	base	watts	item number	description	avg rated life (hrs)	lumens	dimnable
MR-16	GU5.3	3	398-03	3WMR16,12V, LED, WW	25,000	170	no
PAR20	med	5	398-20	5WPAR20,120V, LED, CW	25,000	500	no
PAR20	med	7	398-27	7WPAR20,120V, LED, 2700K	25,000	525	yes
PAR20	med	6	398-28	6WPAR20,120V, LED, 2700K (equiv 50W)	25,000	500	yes
R14	med	4	398-1300	4WR14, 120V, LED, 2700K	25,000	250	yes

Contact factory for other lamp options.