




Project:	Туре:
Item. No.	
Location:	
Notes:	

LightWave

RGBW flexible LED sheet



specifications

electrical

• Electrical rating: 24V DC

• Wattage: 44W

• PCB Type: FPC 35um/35um

• IP rating: IP20

optical characteristics

• Lamp source: LED

• Color temperature: Red, Green, Blue,

White (5000K)

• Beam angle: White (5000K) 120°

mounting/installation

- Installation method: 3M Double-sided tape
- Connectors: 16pcs input/output on board
- Can be linked with connecting cables (included), maximum 88W (up to two sheets)
- Field cuttable: Can be cut at each LED in 1.0" segments

• 12" x 24" x 9/32" (305 x 610 x 7mm)

• 5 years











ordering information

size: 305x610mm (12"x24")

4x12x24=1152LEDs

RGBW

item number	sheet size	LED type	LED qty	color temp (k)	lumens (lm)	Ra	power	beam angle
LW1224-RGBW-44	12" x 24" x 9/32" (305 x 610 x 7mm)	RGBW	4 x 288	Red, Green, Blue, 5000K	Red - 200 Green - 880 Blue - 150 White - 1180	>80 white (5000K)	4 x11W	120° white (5000K)

standard accessories included: Connection cables: two 2.05" (52mm) and two 5.90" (150mm)

123024