


LightWave



Spec Sheet Single Color Flexible LED Sheet

Project:	Type:
Item. No.	
Location:	
Notes:	

single color flexible LED sheet

specifications

electrical

• Electrical rating: 24V DC

Wattage: 20WIP rating: IP20

optical characteristics

• Lamp source: LED

• Color temperature:

-Stock: 3000K, 5000K, 6500K -Special order: 2700K, 4,000K

• Beam angle: 120°

mounting/installation

- Installation method: 3M Double-sided tape
- Connectors: 16pcs input/output on board
- Can be linked with connecting cables (included), maximum 80W (up to four sheets)
- Field cuttable: Can be cut at each LED in 0.66" segments

dimensions

• 12" x 24" x 9/32" (305 x 610 x 7mm)

warranty

• 3 years



see ordering information on next page

031925



individual sheets

item number	sheet size	LED type	LED qty	color temp (k)	lumens	Ra	power	beam angle
LW1224-27K-20				2700K*	2080			
LW1224-30K-20	12" x 24" x 9/32"	single color	648	3000K	2080	>80	20W	120°
LW1224-40K-20	(305 x 610 x 7mm)	COIOI	COIOI	4000K*	2100			
LW1224-50K-20				5000K	2100			
LW1224-65K-20				6500K	2160			

included with each sheet: two 2.0" and two 5.90" connection cables

kits

item number	color temperature (k)	description
LW1224-27K-20-K4	2700K*	Kit includes four LED sheets, eight 2" connecting cables, eight 5.9" connecting cables, one 60" driver input cable, one cable management set
LW1224-30K-20-K4	3000K	Kit includes four LED sheets, eight 2" connecting cables, eight 5.9" connecting cables, one 60" driver input cable, one cable management set
LW1224-40K-20-K4	4000K*	Kit includes four LED sheets, eight 2" connecting cables, eight 5.9" connecting cables, one 60" driver input cable, one cable management set
LW1224-50K-20-K4	5000K	Kit includes four LED sheets, eight 2" connecting cables, eight 5.9" connecting cables, one 60" driver input cable, one cable management set
LW1224-65K-20-K4	6500K	Kit includes four LED sheets, eight 2" connecting cables, eight 5.9" connecting cables, one 60" driver input cable, one cable management set

^{*}Denotes special order

accessories

item number	description
LW-IC60	Input cable - 60" required to connect LED sheet to driver
LW-CC2	Connecting cable - 2"
LW-CC5.9	Connecting cable - 5.9"
LW-SPACER	Spacer set, includes 8 spacers with screws and adhesive stickers

^{*}Denotes special order