


Spec Sheet	Single	Color	Flexible	LED	Sheet

Project:	Type:
Item. No.	
Location:	
Notes:	

LightWave

Single Color flexible LED sheet



specifications

electrical

• Electrical rating: 24V DC

• Wattage: 20W

• PCB Type: FPC 35um/35um

• IP rating: IP20

optical characteristics

• Lamp source: LED

• Color temperature: 2700K, 3000K,

4000K, 5000K, 6500K • Beam angle: 120°

mounting/installation

- Installation method: 3M Double-sided tape
- Connectors: 16pcs input/output on board
- Can be linked with connecting cables (included), maximum 80W (up to four sheets)
- Field cuttable: Can be cut at each LED in 0.66" segments

• 12" x 24" x 9/32" (305 x 610 x 7mm)

• 5 years







٠	K	1	0		(0)	X	1	0	(0)	0	Ki.	×		٠	(e)	K.	kê	X	X		٠	(0)	(0)	6	(0)	(0)	Kô)	(0)	(0)	X.	X.	X.	×.	X.	×.	×.	X.	X3	Ú
4	*	*	•	•		*	*	•	•		*	X	• *	•		*	*	*	X		•	•			¥ 🙃	(0)			*	× •	* •	×.	* •	*.	*	X	X.	*	X
٠	X.	X	0	0	•	X	X	•			10	X		٦			1	X	X		•		(0)			(0)	(0)	(0)		X.	X.	X.	X.	X	X.	¥.	X		X
	マブ	茶	•	0		1	X	•			中人	X	0 1	(6)		**************************************	Y.	X	X	0 7			Y D	P ()	マバー	TO A		1	4.7. 4.0.	X.	X.	X	X.	X	X	X	***	A.	X
	学が	*	•			**	*	•			***	*	- X			**	**	*	菜	0 7	0			*	*	*			*	**	**	*	X.	**	**	*	*	*	*(
()	* ·	1	•		(0)	X		•	()	×	*	×	0 4		(0)		***	1	求	×-0		0		P-X-	* 0	()	(0)	()	1 0	**	X.	X.	**	**	**	X.	**	*	X.
(i)	* *	*				X	×		(0)		***	X	- X			**	¥.	X	X		•		X D	X B	**	× O	× •	× i		* * * * * * * * * * * * * * * * * * *	×.	X	X.	X	X.	Ż.	X.	**	X
	中が	*	•	0		*	*	•	(a)	*	* 0	*	. *	6			* 0	*	菜	0 4			* 0	* 0	* 0	1	(0)		*	**	**	**	**	×.	**	*	**	**	*
•	今 ラ 米。	水		·×	K.	*	×	•	•	← ×.	*.*	*. *.	八十	×	- ×-	* 米	♦ ->< 	*	**	×-4		***	♦- X-	Φ-X- 	* / 。	◆->< -><	← ×- Κ •)	4-)<><><><><><><><><><	◆ % * □	* 1	** **	**	**	*	**	菜	**	*************************************	*
	*	×			1	X	×				*	X	• ×		0	× a	×.	X	X	n ×	•	0	¥ o	10	X.	* a	¥ •		X.	**	*	*	*	*	**	Ť.	**	**	*
	* F	*	•	•		X					* 0	*	-	3	· ·		* •	***	菜					·X-			× ·	X	* .	**	*	**	***		* ·	*	**	* •	X
Õ	幸力 米.■	*		0		学 / ×、	· · ·	0		γ.×.	今六 ×□	*	**	٥	K.	♦ ↑ × □	**	X	X	×-9		(0)	X D	φ.Χ. Χ.Β.	** **	***	X D	(0)	**	* × •	**	**	** **	X.	X.	X.	***		4-) X
	*	*	•		* 0	*	*	•	0		**	米	-*	3	k		* 0	*	菜	×-0	(0)		10	φ-X- *(B)	*	10	*(0)	()	*	**	**	*	*	*	**	*	**	**	×.
Õ	*	*			K.	少小	*			K B	水田	*	- X			米里	**	*	米	8		0	* B	K.	米	火	*	K	**	**	***	*	**	*	**	X.	**	水	*
(8)	X.	X	•	0		X	T.				YB	X	- Y	•	× 0		Y	X	求		•		Y a			10	(1)	(0)	1	X.	Y B	T.	X.	X.	**	*	Y.	10	X
0	φ> X.	*				*	(*) (*) (*)			×	φ.×	X	-	3	K.	♦ ×	ф-X	X	菜	X-		*	∳-X	φ×-	◆ 米	***		φ-)<- (□)	4 ×	ф:X	**	X	**	**	**	*	**	φ ->(* • •	サン
(*	*	0	0		*	*		•		**	*	- *		(0)	**	**	*	*	0 7					**	*	* •	*	**	**	**	**	*	**	**	*	*	**	*
	*	1				*	1	•	(0)	0	*	*	-		0	10	**	1	1			*	10	Φ-X-	**	浴	10	X		**	T'a	T.	**	1	**	T'	**	**	*

610mm / 24"

ordering information

item number	sheet size	LED type	LED qty	color temp (k)	lumens	Ra	power	beam angle
LW1224-27K-20				2700K	2080			
LW1224-30K-20	12" x 24" x 9/32"	single color	648	3000K	2080	>80	20W	120°
LW1224-40K-20	(305 x 610 x 7mm)	00101		4000K	2100			
LW1224-50K-20				5000K	2100			
LW1224-65K-20				6500K	2160			

standard accessories included: Connection cables: two 2.05" (52mm) and two 5.90" (150mm)

052924